

Slurry knife gate valves operate in some of the harshest and most remote locations on earth. In these challenging applications, operators often concede routine valve failure, but this comes at a hefty price of downtime and valve replacement costs. There must be a better solution...

An ineffective seal at valve closure can increase the rate of failure in a slurry knife gate valve and heighten the chance of a high-pressure downstream leak, putting personnel and plant at risk.

Due to highly erosive and abrasive process conditions, most severe service knife gate valves must be replaced due to excessive body wear.

Knife gate valves without a full round port in slurry service experience significantly more turbulence and fail earlier than valves with a full round port.

Valves in severe slurry service can require downtime for maintenance or replacement multiple times per year, lowering productivity and increasing operating costs.









challenges with a single valve?

What if you could solve these



Now you can with the Clarkson KS1 Knife Gate Valve 🕨



Clarkson[™] KS1 Knife Gate Valves

Upgrade your severe service knife gate valves to extend valve life and service intervals, and lower total cost of ownership.

Discover enduring zero leakage sealing performance



Deploy a patented gate edge seal that creates a continuous seal around the gate, together with a precision-molded elastomer seat to deliver zero leakage. This heavy-duty replaceable seat increases the contact area and resilient sealing ability of the valve compared to standard O-ring designs, resulting in superior isolation performance over an extended lifecycle.

Perform in heavy slurry conditions



Run your processes for longer with a valve design optimized to thrive in heavy slurry conditions. A full round port eliminates protrusions into the flow, minimizing turbulence across the valve to extend body life. This not only ensures the longevity of sealing components, but also minimizes the damaging impacts of slurry on downstream pipeline equipment.

Defend your sealing elements



Extend the life of your valves with standard inlet and outlet hardened wear rings to protect the sealing elements and body from abrasive slurry. These durable Ni-Resist rings can be rotated 3 times through 4 positions to extend valve life and replacement intervals, allowing you to improve your asset utilization and process productivity.

Return to production at speed



Minimize valve repair downtime with external packing adjustments that dynamically self-adjust pressure to the gate edge seal system. Repairs can be performed rapidly using standard tools and readily available spare parts. The valve is also designed to MSS-SP-135 face-to-face dimensions for simple changeout and upgrade of your underperforming valves.

© 2021 Emerson Electric Co. All rights reserved.

Neither Emerson, Emerson Automation Solutions, nor any of their affiliated entities assumes responsibility for the selection, use or maintenance of any product. Responsibility for proper selection, use, and maintenance of any product remains solely with the purchaser and end user.

Clarkson is a mark owned by one of the companies in the Emerson Automation Solutions business unit of Emerson Electric Co. Emerson Automation Solutions, Emerson and the Emerson logo are trademarks and service marks of Emerson Electric Co. All other marks are the property of the irrespective owners. The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available upon request. We reserve the right to modify or improve the designs or specifications of such products at any time without notice.

